

# CRY-CHAS-1705HB

## Specification



### Features

- Modular mechanism design provides flexible product configuration and easy maintenance.
- Optional to built-in touch screen for interactive application
- Optional with auto-brightness sensor offers application in day and night.
- Optional transfective panel for sunlight readable application

### CRY-CHAS-1705HB Specification

<b>Panel</b>	<b>Cell Type / Glass Surface</b>	TFT LCD / Black Anti-Glare, low reflection coating	
	<b>Aspect Ratio / Size</b>	4 : 3 / 17" viewable diagonal area	
	<b>Active Area / Pixel Pitch</b>	337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm	
	<b>Native Resolution / Colors</b>	1280(H) x 1024(V) / 16.7 Million	
	<b>Brightness / Contrast</b>	700 cd/m <sup>2</sup> (typ) / 500 : 1	
	<b>Response Time</b>	5 ms	
	<b>Viewing Angle (typical)</b>	H. 150° (- 75° ~ + 75°) , V. 130°(- 70° ~ + 60°)	
	<b>Light Source</b>	CCFL , Long life, 50,000 hrs (typ)	
<b>Input Sources</b>	<b>PC System</b>	<b>Signal</b>	Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)
		<b>Sync</b>	Separate Sync, Composite Sync, Sync On Green
		<b>Frequency</b>	F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz
	<b>Audio System</b>	2W speaker x 2	
<b>Input Terminals</b>	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Outlet		
<b>Convenient Features</b>	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)		
<b>Power</b>	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
<b>Power Consumption</b>	<b>Operation / Power Saving</b>	30 watt , < 2 watt (Support DPMS)	
<b>Operating Condition</b>	<b>Temperature / Humidity</b>	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
<b>Storage Condition</b>	<b>Temperature / Humidity</b>	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
<b>Certification</b>	FCC , CE		
<b>Dimensions</b>	<b>Physical</b>	With Base(W x H x D) : TBD	
		Without Base(W x H x D) : 379.7 x 318.4 x 59.8 mm	
	<b>Carton</b>	W x H x D = 416 x 425 x 142 mm	
<b>Weight</b>	<b>N.W. / G.W.</b>	5.0 Kgs / 6.0 Kgs	
<b>Container Loaded</b>	<b>20ft / 40ft / 40ft HQ</b>	1040 / 2160 / NA (Sets , By pallet)	

<b>Options</b>	<b>Touch</b>	<b>Video / TV</b>	<b>Enhanced Panel</b>	<b>Others</b>
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sun Light Readable	Light Ssensor
	Protected glass		Transfective	Auto-Dimming



**Crystal Display Electronics AG**

Zürcherstrasse 37a  
Tel.: 055 451 54 54  
www.crystal-cde.com

8852 Altendorf  
Fax: 055 451 54 59  
www.movebox.com